

AMENDMENTS TO THE CLAIMS

A complete set of the existing claims are set forth below, with the amended claims showing deletions (~~strike-through~~) and insertions (underline).

1. (Cancelled)
2. (Cancelled)
3. (Currently amended) A register file, comprising:~~The register file of claim 2~~
a multi-level multiplexer output circuit coupled to a global bit trace, said multi-level multiplexer output circuit comprises a plurality of local bit traces;
keeper circuitry coupled to said global bit trace and a driving signal trace; and
decoder circuitry coupled to said keeper circuitry to selectively decouple the driving signal trace from said global bit trace;
~~further comprising~~ a plurality of select signal traces corresponding to said plurality of local bit traces; and
wherein said decoder circuitry is designed to:
determine whether one of said plurality of local bit traces evaluates;
determine if one of said plurality of select signal traces, corresponding to the evaluated bit trace, is asserted; and
conditionally decouple said driving signal trace from said global bit trace, based at least in part on the results of said determines.
4. (Original) The register file of claim 3 wherein said conditionally decoupling occurs upon determining one of said plurality of local bit traces evaluates and determining one of said plurality of select signal traces, corresponding to said evaluated bit trace, is asserted.

5. (Original) The register file of claim 3 wherein said decoder is designed to perform said determining if one of said plurality of local bit traces evaluates by determining whether one of a plurality of row select signals and one of a plurality of data output signals couples one of said plurality of local bit traces to a first supply node.
6. (Original) The register file of claim 3 wherein said keeper circuitry comprises a P-type MOS transistor with a source coupled to said driving signal trace and a drain coupled to said global bit trace, and said selective decoupling of said driving signal trace from said global bit trace comprises turning off said P-type MOS transistor.
7. (Currently amended) The register file of claim ~~32~~ wherein said local bit traces are coupled to a supply node through corresponding local bit trace precharge circuitries.
8. (Original) The register file of claim 7 wherein said local bit trace precharge circuitries comprise a P-type MOS transistor and an N-type MOS transistor, wherein a drain of said P-type MOS transistor is coupled to a power supply trace and a source of said P-type MOS transistor is coupled to a drain of said N-type MOS transistor and wherein a drain of said N-type MOS transistor is coupled to a corresponding local bit trace.
9. (Original) The register file of claim 8 wherein a gate of said P-type MOS transistor is coupled to a clock line and a gate of said N-type MOS transistor is coupled to said power supply trace.
10. (Currently amended) The register file of claim ~~124~~ wherein said keeper circuitry comprises a weak P-type MOS transistor.
11. (Currently amended) The register file of claim ~~124~~ further comprising a precharge transistor to precharge said global bit trace.

12. (Currently amended) ~~The~~A register file, comprising:
a multi-level multiplexer output circuit coupled to a global bit trace;
keeper circuitry coupled to said global bit trace and a driving signal trace;
decoder circuitry coupled to said keeper circuitry to selectively decouple the
driving signal trace from said global bit trace; and
~~of claim 4~~ wherein said multi-level multiplexer output circuit comprises a 3-stack pulldown.
13. (Currently amended) The register file of claim 124 wherein said multi-level multiplexer output circuit comprises a plurality of low threshold voltage transistors.
14. (Original) A method comprising:
determining if one of a plurality of local bit traces evaluates;
determining if one of a plurality of select signals on select signal traces,
corresponding to local bit traces, is asserted; and
conditionally decoupling a driving signal trace from a global bit trace, based at least in part on the results of said determining operations.
15. (Original) The method of claim 14 wherein said conditionally decoupling occurs upon determining one of said plurality of local bit traces evaluates and determining one of said plurality of select signal traces, corresponding to said evaluated bit trace, is asserted.
16. (Original) The method of claim 14 wherein said determining if one of a plurality of local bit traces evaluates comprises determining whether one of a plurality of row select signals and one of a plurality of data output signals couples one of said plurality of local bit traces to a first supply node.
17. (Original) The method of claim 14 wherein said conditionally decoupling a driving signal trace from a global bit trace comprises turning off a switching element.

18. (Original) The method of claim 17 wherein said switching element is a weak P-type MOS device.

19. (Cancelled)

20. (Cancelled)

21. (Currently amended) ~~A system comprising; The system of claim 20~~
a processor having;
a register file output signal trace;
a driving signal trace; and
a register file including;
a global bit trace coupled to said register file output signal trace;
a multi-level multiplexer output circuit coupled to said global bit trace, said
multi-level multiplexer output circuit comprises a plurality of local bit
traces;
keeper circuitry coupled to said global bit trace and the driving signal
trace; and
decoder circuitry coupled to said keeper circuitry to selectively decouple
the driving signal trace from said global bit trace;
a memory configured to store data;
a bus coupled to the processor and memory to facilitate data exchange between
the processor and memory;

wherein said register file further comprises a plurality of select signal traces corresponding to said plurality of local bit traces and wherein said decoder circuitry operates to:

determine whether one of said plurality of local bit traces evaluates;
determine whether one of said plurality of select signal traces, corresponding to said evaluated bit trace, is asserted; and

conditionally decouple said driving signal trace from said global bit trace, based at least in part on the results of said determined operations.

22. (Original) The system of claim 21 wherein said conditionally decoupling occurs upon determining one of said plurality of local bit traces evaluates and determining one of said plurality of select signal traces, corresponding to said evaluated bit trace, is asserted.

23. (Original) The system of claim 21 wherein said determining if one of said plurality of local bit traces evaluates comprises determining whether one of a plurality of row select signals and data output signals couples said local bit trace to a first supply node.

24. (Original) The system of claim 21 wherein said keeper circuitry comprises a P-type MOS transistor with a source coupled to said driving signal trace and a drain coupled to said global bit trace and wherein said intelligent decoupling said driving signal trace from said global bit trace comprises turning off said P-type MOS transistor.

25. (Currently amended) The system of claim ~~2149~~ wherein said keeper circuitry comprises an upsized P-type MOS transistor.

26. (Currently amended) The system of claim ~~2149~~ wherein said multi-level multiplexer output circuit comprises a plurality of low threshold voltage transistors.

27. (Currently amended) The system of claim ~~2149~~ wherein the system further comprises a graphic controller coupled to the bus.